
## GPS/Glonass SMD Antenna



Glonass-184-SMD	
Beyondoor	
China	
-	
50 pc	
	Beyondoor China

## **Product Description**

Model: BY-GPS-GLONASS -184-SMD

Antenna

Nominal Frequency (MHz): 1590

10dB Bandwidth (MHz): 10

Return loss at center Frequency dB max -20.0

Gain(Zenith 90°) dBi type: 2.0

Impedance (Ω): 50

Axial Ratio dB max: 3.0

Polarization Model: RHCP

Frequency Temperature Coefficient: 20ppm/deg.°C max

. Center frequency: -10dB bandwidth center frequency depend on the ground plane of customer

· Mounting method: SMD mount

(ii) Mechanical

Weight (gram) <10</li>

Size (mm): 18×18×4

(iii) Environmental

Working Temp: -40°C~+85°C

Storage Temp: -45°C~+90°C

Vibration: Sine sweep 1g(0-p)10~50~10Hz each axis

. Humidity: Humidity95%~100%RH

\_\_\_\_\_

JIAXING BEYONDOOR ELECTRONICS CO.,LTD

Address: #101, Weiyi West Road, Dongzha Economic Zone ,Jiaxing 314000, Zhejiang, China

Website:www.beyondoor.com E-MAIL: frank@beyondoor.com MSN:firstgps@hotmail.com SKYPE NAME:beyondoorgps